

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 2 of 18

**In the Claims:**

1. (Currently Amended) An *in ovo* injection apparatus, comprising:  
an egg carrier that holds a plurality of eggs and provides external access to the eggs;  
a plurality of injection devices positioned above the carrier, wherein each injection device is configured to contact a respective egg in the carrier and deliver a predetermined dosage of a treatment substance into the egg and/or remove material from the egg; and  
an egg support assembly positioned beneath the carrier that is configured to solidly support each egg in the carrier during contact therewith by a respective injection device and to prevent each egg from being pushed downwardly into the carrier by a respective injection device.
2. (Currently Amended) The apparatus of Claim 1, wherein the egg support assembly comprises:  
a frame movable between an operative position and a retracted position;  
a plate attached to the frame and comprising an array of openings formed therein; and  
a plurality of pedestals, each pedestal removably and snugly secured within a respective one of the openings, wherein each pedestal comprises a free end portion configured to engage an egg within the carrier when the frame is in the operative position.
3. (Original) The apparatus of Claim 2, wherein the egg support assembly is operatively associated with the plurality of injection devices such that each pedestal moves upwardly through a respective opening in the carrier to support an egg as a respective injection device makes contact with the egg.
4. (Original) The apparatus of Claim 1, wherein the egg support assembly is configured to lift each egg from the carrier during contact with each egg by a respective injection device.

**BEST AVAILABLE COPY**

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 3 of 18

5. (Original) The apparatus of Claim 2, wherein a height of the free end portion of each pedestal relative to the plate is adjustable.

6. (Currently Amended) The apparatus of Claim 5, wherein the a height of the free end portion of each pedestal relative to the plate is adjustable via one or more shims disposed between the free end portion and the plate.

7. (Currently Amended) The apparatus of Claim 2, wherein each pedestal includes a proximal end opposite from the free end portion, and wherein an O-ring is secured to the proximal end that provides a snug, friction fit when the proximal end is disposed within a respective one of the plate openings.

8. (Currently Amended) The apparatus of Claim 2, wherein each pedestal free end portion has a concave configuration.

9. (Currently Amended) The apparatus of Claim 8, wherein each pedestal free end portion comprises a wall that is inclined relative to a centerline of the pedestal that is between about twenty five degrees and about fifty five degrees (25°-55°).

10. (Original) The apparatus of Claim 2, wherein the support assembly frame is movable via actuators selected from the group consisting of pneumatic actuators, hydraulic actuators, electronic actuators, and electromagnetic actuators.

11. (Currently Amended) An *in ovo* injection apparatus, comprising:  
an egg carrier that holds a plurality of eggs and provides external access to the eggs;

a plurality of injection devices positioned above the carrier, wherein each injection device is configured to contact a respective egg in the carrier and deliver a

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 4 of 18

predetermined dosage of a treatment substance into the egg and/or remove material from the egg; and

an egg support assembly positioned beneath the carrier that is configured to solidly support each egg in the carrier, wherein the egg support assembly prevents each egg from being pushed downwardly into the carrier by a respective injection device, and wherein the egg support assembly lifts and lift each egg upwardly from the carrier during contact therewith by a respective injection device, wherein the egg support assembly comprises:

a frame movable between an operative position and a retracted position;

a plate attached to the frame and comprising an array of openings formed therein; and

a plurality of pedestals, each pedestal removably and snugly secured within a respective one of the openings, wherein each pedestal comprises a free end portion configured to engage an egg within the carrier when the frame is in the operative position.

12. (Original) The apparatus of Claim 11, wherein the egg support assembly is operatively associated with the plurality of injection devices such that each pedestal moves upwardly through a respective opening in the carrier to support an egg as a respective injection device makes contact with the egg.

13. (Original) The apparatus of Claim 11, wherein a height of the free end portion of each pedestal relative to the plate is adjustable.

14. (Currently Amended) The apparatus of Claim 13, wherein the a height of the free end portion of each pedestal relative to the plate is adjustable via one or more shims disposed between the free end portion and the plate.

15. (Currently Amended) The apparatus of Claim 11, wherein each pedestal includes a proximal end opposite from the free end portion, and wherein an O-ring is

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 5 of 18

secured to the proximal end that provides a snug, friction fit when the proximal end is disposed within a respective one of the plate openings.

16. (Currently Amended) The apparatus of Claim 11, wherein each pedestal free end portion has a concave configuration.

17. (Currently Amended) The apparatus of Claim 16, wherein each pedestal free end portion comprises a wall that is inclined relative to a centerline of the pedestal that is between about twenty five degrees and about fifty five degrees (25°-55°).

18. (Original) The apparatus of Claim 11, wherein the support assembly frame is movable via actuators selected from the group consisting of pneumatic actuators, hydraulic actuators, electronic actuators, and electromagnetic actuators.

19. (Currently Amended) An *in ovo* injection apparatus, comprising:  
an egg carrier that holds a plurality of eggs and provides external access to the eggs;

a plurality of injection devices positioned above the carrier, wherein each injection device is configured to contact a respective egg in the carrier and deliver a predetermined dosage of a treatment substance into the egg and/or remove material from the egg; and

an egg support assembly positioned beneath the carrier that is configured to solidly support each egg in the carrier during contact therewith by a respective injection device, and prevent each egg from being pushed downwardly into the carrier by a respective injection device, wherein the egg support assembly comprises:

a frame movable between an operative position and a retracted position;

a plate attached to the frame and comprising an array of openings formed therein; and

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 6 of 18

a plurality of pedestals, each pedestal removably and snugly secured within a respective one of the openings, wherein each pedestal comprises a concave free end portion configured to engage an egg within the carrier when the frame is in the operative position, and wherein a height of the free end portion of each pedestal relative to the plate is adjustable.

20. (Original) The apparatus of Claim 19, wherein the egg support assembly is operatively associated with the plurality of injection devices such that each pedestal moves upwardly through a respective opening in the carrier to support an egg as a respective injection device makes contact with the egg.

21. (Original) The apparatus of Claim 19, wherein the egg support assembly is configured to lift each egg from the carrier during contact with each egg by a respective injection device.

22. (Original) The apparatus of Claim 19, wherein a height of the free end portion of each pedestal relative to the plate is adjustable via one or more shims disposed between the free end portion and the plate.

23. (Currently Amended) The apparatus of Claim 19, wherein each pedestal includes a proximal end opposite from the free end portion, and wherein an O-ring is secured to the proximal end that provides a snug, friction fit when the proximal end is disposed within a respective one of the plate openings.

24. (Currently Amended) The apparatus of Claim 19, wherein each pedestal free end portion comprises a wall that is inclined relative to a centerline of the pedestal that is between about twenty five degrees and about fifty five degrees (25°-55°).

In re: Gross et al.  
Serial No.: 10/686,762  
Filed: October 16, 2003  
Page 7 of 18

25. (Original) The apparatus of Claim 19, wherein the support assembly frame is movable via actuators selected from the group consisting of pneumatic actuators, hydraulic actuators, electronic actuators, and electromagnetic actuators.

26. (Currently Amended) A method of injecting eggs *in ovo*, comprising:  
positioning an egg carrier containing a plurality of eggs beneath a plurality of injection devices, wherein each injection device is configured to contact a respective egg in the carrier and deliver a predetermined dosage of a treatment substance into the egg and/or remove material from the egg; and

supporting the plurality of eggs from beneath the egg carrier while simultaneously delivering a predetermined dosage of a treatment substance into each egg and/or removing material from each egg such that the eggs are prevented from being pushed downwardly into the carrier by a respective injection device.

27. (Currently Amended) The method of Claim 26, wherein supporting the plurality of eggs comprises positioning an egg support assembly beneath the egg carrier, wherein the egg support assembly comprises:

a frame movable between an operative position and a retracted position;  
a plate attached to the frame and comprising an array of openings formed therein; and

a plurality of pedestals, each pedestal removably and snugly secured within a respective one of the openings, wherein each pedestal comprises a free end portion configured to engage an egg within the carrier when the frame is in the operative position.

28. (Original) The method of Claim 26, wherein supporting the plurality of eggs comprises lifting the eggs upwardly from the egg carrier.

29. (Currently Amended) The method of Claim 26, wherein each pedestal free end portion has a concave configuration.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**